

Appendices

Appendix A: The RINEX navigation file format

Appendix B: Statistics for the orbit solutions

Appendix C: Statistics for the orbit solutions for the satellites as viewed from station 'tmgo'

Appendix D: The errors in the orbits of the satellites

Appendix E: The errors in the orbits of the satellites as viewed from station 'tmgo'

Appendix A: The RINEX navigation file format

The format of the RINEX (Receiver Independent Exchange Format) Version 2 is described in an document [Ref. 5]. The next two pages show the description of the navigation message file that contains the orbital parameters of the GPS satellites.

TABLE A3 NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION		
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
RINEX VERSION / TYPE	- Format version (2) - File type ('N' for Navigation data)	I6,14X, A1,19X
PGM / RUN BY / DATE	- Name of program creating current file - Name of agency creating current file - Date of file creation	A20, A20, A20
* COMMENT	Comment line(s)	A60
* ION ALPHA	Ionosphere parameters A0-A3 of almanac (page 18 of subframe 4)	2X,4D12.4
* ION BETA	Ionosphere parameters B0-B3 of almanac	2X,4D12.4
* DELTA-UTC: A0,A1,T,W	Almanac parameters to compute time in UTC (page 18 of subframe 4) A0,A1: terms of polynomial T : reference time for UTC data W : UTC reference week number. Continuous number, not mod(1024)!	3X,2D19.12, 2I9
* LEAP SECONDS	Delta time due to leap seconds	I6
END OF HEADER	Last record in the header section.	60X

Records marked with * are optional

TABLE A4 NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
PRN / EPOCH / SV CLK	- Satellite PRN number - Epoch: Toc - Time of Clock year (2 digits) month day hour minute second - SV clock bias (seconds) - SV clock drift (sec/sec) - SV clock drift rate (sec/sec ²)	I2, 5I3, F5.1, 3D19.12

Determination of the accuracy of the GPS Broadcast Orbit and the WAAS-corrected Orbit

BROADCAST ORBIT - 1	<ul style="list-style-type: none"> - IODE Issue of Data, Ephemeris - Crs (meters) - Delta n (radians/sec) - M0 (radians) 	3X,4D19.12
BROADCAST ORBIT - 2	<ul style="list-style-type: none"> - Cuc (radians) - e Eccentricity - Cus (radians) - sqrt(A) (sqrt(m)) 	3X,4D19.12
BROADCAST ORBIT - 3	<ul style="list-style-type: none"> - Toe Time of Ephemeris (sec of GPS week) - Cic (radians) - OMEGA (radians) - CIS (radians) 	3X,4D19.12
BROADCAST ORBIT - 4	<ul style="list-style-type: none"> - i0 (radians) - Crs (meters) - omega (radians) - OMEGA DOT (radians/sec) 	3X,4D19.12
BROADCAST ORBIT - 5	<ul style="list-style-type: none"> - IDOT (radians/sec) - Codes on L2 channel - GPS Week # (to go with TOE) Continuous number, not mod(1024)! - L2 P data flag 	3X,4D19.12
BROADCAST ORBIT - 6	<ul style="list-style-type: none"> - SV accuracy (meters) - SV health (MSB only) - TGD (seconds) - IODC Issue of Data, Clock 	3X,4D19.12
BROADCAST ORBIT - 7	<ul style="list-style-type: none"> - Transmission time of message (sec of GPS week, derived e.g. from Z-count in Hand Over Word (HOW)) - spare - spare - spare 	3X,4D19.12